

P-5 Wash Light

Specifications		
Optics	Light source	44 x High power 10W RGBW LEDs
	LEDs expected lifetime	50,000 hours*
	Interchangeable lens option	15°, 21° & 43°
Photometric	Light output	23,500 lumen (43° lens)
	Efficacy	58 lm/W
Features	Tilt	0 - 190°
Electrical	AC Power	208 - 240 V Nominal 50/60 Hz
	Maximum power consumption	450 W (all LEDs on)
	Typical power consumption	420 W (all LEDs on)
	Power factor	0.98 PF (230 V)
Programming and Control	Protocol	USITT DMX512 A
	Setting and addressing	Wireless DMX (LumenRadio) RDM Stand alone mode (programmable by RFID) Oled graphical display / 4 buttons Software upgradeable via Uploader cable (P/N:83062011)
	DMX channels	3, 4, 6, 8, 9 or 10
Physical	Dimensions (L x H x W)	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in)
	Weight	8.9 kg (19.6 lbs.)
	Material	Aluminium
	Lens	PE and tempered glas front
	IP class	IP65
Installation	Mounting	Any
	Rigging possibilities	Floor stand (included) or hanging (Omega Clamps included)
	Safety features	Bottom mount for Safety wire
Thermal	Temperature range, Operating	-10° - 40°C (-14° - 104°F)
	Temperature range, Start-up	-10° - 40°C (-14° - 104°F)
	Humidity (max.)	98%
	Cooling	Active, Forced air, temperature-regulated, low noise
Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out Power cable 0.5m with bare ends
Certified to Conforms to	CSA Std. C22.2 No. 166	
	UL Std. 1573	
	2006/95/EC: Low Voltage Directive	EN 60598-1, EN 60598-2-17, EN 62471
	2004/108/EC: EMC Directive	EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3
	RoHS2 Directive	2011/65/EU
Included Items	Included Items	Floor Stand (incl. screws) 2 pcs Omega brackets Wireless DMX G4 antenna User manual Neopren pouch
Fixtures and Accessories	Fixtures	Order no: 80030517 - P-5 Wash Light (43°) Order no: 80030515 - P-5 Wash Light (21°) Order no: 80030518 - P-5 Wash Light (15°)
	Lens/s	Order no: 83061118 - P-5, Lens kit (43°) Order no: 83061117 - P-5, Lens kit (21°) Order no: 83061116 - P-5, Lens kit (15°)
	Brackets	Order no: 83060603 - BCC-2 Dual bracket Order no: 83060604 - BCC-4 Quad bracket Order no: 83060602 - Omega bracket
	Floorstand	Order no: 83060610 - Floorstand for P, Q and X series with 1/4-turn fasteners
	Barndoor	Order no: 83061119 - Accessory Holder P Series Order no: 83061120 - Barndoor 4-way Order no: 83061121 - Barndoor 8-way Order no: 83061122 - Color frame
	Cables	Order no: 83062011 - SGM USB uploader cable
	Flight case	Order no: 82051501 - Flight case for 4 pcs of P-5/Q-7/X-5 Order no: 82051502 - Flight case for 4 pcs of P-5/Q-7/X-5 incl. Barndoors

*(Figure provided by manufacturer and obtained under manufacturer's test conditions)