



Rogue R2 Beam

Rogue R2 Beam is the light cannon of the Rogue series, boasting an intense 133,200 lux at 15 meters with its Osram Sirius 230 W HRI lamp. Rogue R2 Beam comes with 14 fixed colors in its fully scrollable, variable speed color wheel, which also provides split colors perfectly. Its 8-facet rotating prism provides an endless supply of creative and dynamic beam looks to inspire and elevate design options. Learn more at chauvetrogue.com.



AT A GLANCE

- Powerful 1-degree beam, 133,200 lux @ 15 m
- 17 gobos with continuous variable-speed wheel scroll
- 8-facet rotating prism for incredible gobo and beam effects
- Color wheel with 14 colors, split color ability, and continuous variable-speed scrolling
- Neutrik powerCON power input connection
- Intense 230 W Osram Sirius HRI lamp
- 3- and 5-pin DMX input/output connections
- Simple and complex DMX channel profiles for programming versatility

Specifications

Optical

- Light Source: Osram Sirius 230 W lamp, 8000 K, 2,500 hours life expectancy
- Color Temperature (at full): 7500 K
- Beam Angle: 1°
- Field Angle: 2°
- Illuminance (total): 133,200 lux @ 15 m

Dynamic Effects

- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 270° tilt
- Colors: 14 + white, interchangeable, slot-n-lock, split colors, continuous scroll at variable speeds
- Gobos : 17 + open (17 metal), continuous scroll at variable speeds
- Dimmer: Motorized
- Shutter/Strobe: Motorized
- Focus: Motorized
- Frost: Motorized
- Prism: 8 Facets, motorized, rotating
- Strobe Rate: 0 to 20 Hz
- Move in Black: Yes

Construction / Physical

- Dimensions (single unit): 16.1 x 12.9 x 18.7 in (409 x 327 x 474 mm)
- Weight (single unit): 45.00 lb (20.60 kg)
- Exterior Color: Black
- Housing Material: High-impact flame-retardant polymer

Connections

- Power Connection: Edison (Local) plug to Neutrik
- Power Input: Neutrik powerCON
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: DMX
- DMX Channels: 15 or 18
- Modes/Personalities: 2 personalities (15, 18)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 413 W, 3.4 A @ 120 V, 60 Hz
- Power and Current: 393 W, 1.9 A @ 208 V, 60 Hz
- Power and Current: 385 W, 1.7 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE, MET
- IP Rating: IP20, dry location

What's Included

- Rogue R2 Beam
- Neutrik powerCON power cord
- 2 Omega brackets with mounting hardware

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-07
- Neutrik powerCON cables
- DMX Cables
- 230 W Osram Sirius Lamp

