

## G-1 Beam

### LED Moving Head

#### Specifications

<b>Optics</b>	Light source LEDs expected lifetime Beam angle(s) Focus	High-power white LED (6,500K) 50,000 hours* 2.8° 0.3° (Aperture pseudo zoom) Motorized focus
<b>Photometric</b>	Light source output Color temperature	62,000 lux at 3 m (9.8 ft.)* 6,500K
<b>Gobos</b>	Gobo wheel	19 gobos + 2 times open Two oscillation gobo effect areas Gobo shake Continuous scroll CW & CCW
<b>Colors</b>	Color wheel	14 colors + open Split color Continuous scroll CW & CCW
<b>Features</b>	Dimming Strobe Pan / tilt Pan modes: Built-in macro effects Battery status	Electronic Ultra-high-speed strobe effect (1-50 Hz) Endless / 240° 540°, 360°, 360° shortest path, continuous CW, continuous CCW 50 Battery level indicator
<b>Electrical incl. base</b>	AC power, nominal AC power, max. rating Maximum inrush current @ 100VAC Maximum inrush current @ 240VAC Power supply unit Max. power consumption Standby power	100-240V 50/60 Hz 90-264V 50/60 Hz 2.2Amp 6.9Amp Auto-ranging electronic switch-mode 50W 8W
<b>Battery</b>	Battery type Battery capacity (non-stop) Battery capacity (typical use) Battery charge time up to 70% Battery charge time up to 100% Durability Memory effect	Lithium-ion battery 7-9 hours 12-14 hours 8-12 hours 12-16 hours >500 full charge cycles 85% battery capacity after 500 full charge cycles
<b>Electrical excl. base</b>	AC power, nominal Max. power consumption	24VDC 50W
<b>Programming and control</b>	Protocol Setting and addressing Standalone mode Wireless DMX Cabled DMX 16-bit control DMX channels	USITT DMX512A CRMX, W-DMX™ G2, W-DMX™ G3, W-DMX™ G4, W-DMX™ G4S RDM Display/control panel Software upgradable with SGM USB uploader cable (P/N:83062011) 8 internal standalone programs 9 internal pan / tilt presets LumenRadio CRMX 5 pin XLR input/output Dimmer, pan and tilt 12
<b>Physical</b>	Dimensions Weight (incl. 3 batteries) Weight (excl. batteries) Material IP class Color options	Length (base): 219 mm (8.62 in.) Length (head incl. yoke): 288 mm (11.34 in.) Width (base): 255 mm (10.04 in.) Width (head): 150 mm (5.9 in.) Height (base): 90 mm (3.54 in.) Height (head straight up): 382 mm (15.04 in.) 8.9 kg (19.6 lbs.) 8.0 kg (17.6 lbs.) Aluminium, steel, plastic PC/ASA, rubber IP65 White – RAL 9010 Black – RAL 9004 Custom color – any RAL
<b>Installation</b>	Mounting points Orientation Safety features	Two quarter-turn locking points for one Omega bracket Any 2 x attachment points for safety wire Minimum distance to combustible materials: 0.3 m (11 in.) Minimum distance to illuminated surfaces: 0.3 m (11 in.)
<b>Thermal</b>	Temperature range, Operating Temperature range, Start-up Temperature range, Storage Humidity Cooling	-40° to +50°C (-40° to +122°F) -20° to +50°C (-4° to +122°F) -40° to +80°C (-40° to +176°F) 98% Passive
<b>Connections</b>	AC power input DMX data in/out	Neutrik TRUE1 power input connector IP65 Neutrik HD locking XLR 5-pin cable, 0.2 m (7.8 in.)
<b>Conforms to</b>	UL Std. 1573 2014/35/EU: Low Voltage Directive 2014/30/EU: EMC Directive RoHS2 Directive	EN 60598-1, EN 60598-2-17, EN 62471, EN 60529 EN 55103-1, EN 55103-2, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3 2011/65/EU
<b>Included items</b>	Included items	One Omega bracket with 1/4-turn fasteners 2 m power cable with Neutrik TRUE1 power connector User manual
<b>Fixtures and accessories</b>	Fixtures Battery Wireless transmitter Cables Bracket Flightcase	Order no: 80100101 - G-1 Beam, Std, BL, (excl. Batt) Order no: 80100111 - G-1 Beam, Std, WH, (excl. Batt) Order no: 80100191 - G-1 Beam, Std, CU, (excl. Batt) Order no: 80100103 - G-1 Beam, Std, BL, (incl. 3 pcs Batt) Order no: 80100113 - G-1 Beam, Std, WH, (incl. 3 pcs Batt) Order no: 80100193 - G-1 Beam, Std, CU, (incl. 3 pcs Batt) Order no: 83061708 - Battery, Nominal: 21,6V - Nominal: 3350 mAh (1 pcs.) Order no: 80070229 - Lumen Radio CRMX transmitter (DMX only) Order no: 83062011 - SGM USB uploader cable Order no: 07860040 - 2 m power cable with Neutrik TRUE1 Order no: 83060602 - Omega bracket Order no: 83061707 - Ceiling mount for G-1 Order no: 82051004 - Flightcase for 4 pcs. G-1 Beam Order no: 82051005 - Flightcase for 4 pcs. G-1 Beam incl. charger Order no: 42000297 - Charger cable kit for G-1 flightcase (4 pcs.)

\*Figures provided by manufacturer and obtained under manufacturer's test conditions

\*\*Photometrics / SGM Illumination Lab 1.6.0.0

BL = Black (RAL 9004) / WH = White (RAL 9010) / CU = Custom Color (Any RAL color)