

G-1 Beam POI
LED Moving Head

Specifications		
Optics	Light source	High-power white LED (6,500K)
	LEDs expected lifetime	50,000 hours*
Photometric	Beam angle(s)	2.8°
	Focus	0.3°(Aperture pseudo zoom) Motorized focus
Photometric	Light source output	62,000 lux at 3 m (9.8 ft.)*
	Color temperature	6,500K
Gobos	Gobo wheel	19 gobos + 2 times open
		Oscillation effect Gobo shake Continuous scroll CW & CCW
Colors	Color wheel	14 colors + open
		Split color Continuous scroll CW & CCW
Features	Dimming	Electronic
	Strobe	Ultra-high-speed strobe effect (1-50 Hz)
Electrical incl. base	Pan / tilt	Endless / 240°
	Pan modes:	540°, 360°, 360° shortest path, continuous CW, continuous CCW
Electrical incl. base	Built-in macro effects	50
	Dehumidifier	Head
Electrical incl. base	Power/DMX indicator	Yoke
	AC power, nominal	100-240V 50/60 Hz
Electrical incl. base	AC power, max. rating	90-264V 50/60 Hz
	Maximum inrush current @ 100VAC	2.2Amp
Electrical incl. base	Maximum inrush current @ 240VAC	6.9Amp
	Power supply unit	Auto-ranging electronic switch-mode
Electrical incl. base	Max. power consumption	50W
	Standby power	8W
Electrical excl. base	AC power, nominal	24VDC
	Max. power consumption	50W
Programming and control	Protocol	USITT DMX512A
	Setting and addressing	CRMX, W-DMX™ G2, W-DMX™ G3, W-DMX™ G4, W-DMX™ G4S RDM Software upgradable with SGM USB uploader cable (P/N:83062011)
Programming and control	Wireless DMX	LumenRadio CRMX
	Cabled DMX	1 x 5 meter cable for DMX in and out
Programming and control	16-bit control	Dimmer, pan and tilt
	DMX channels	12
Physical	Dimensions	Length (base): 219 mm (8.62 in.)
		Length (head incl. yoke): 288 mm (11.34 in.)
Physical	Weight	Width (base): 255 mm (10.04 in.)
		Width (head): 150 mm (5.9 in.)
Physical	Material	Width (head): 90 mm (3.54 in.)
		Height (base): 90 mm (3.54 in.)
Physical	IP class	Height (head straight up): 382 mm (15.04 in.)
		8.0 kg (17.6 lbs.)
Physical	Corrosion class	Aluminium, steel, plastic PC/ASA, rubber
		IP66
Physical	Color options	CS-M
		White – RAL 9010
Physical	Color options	Black – RAL 9004
		Custom color – any RAL
Installation	Mounting	Two quarter-turn locking points for one Omega bracket
	Orientation	Any
Installation	Safety features	2 x attachment points for safety wire
		Minimum distance to combustible materials: 0.3 m (11 in.) Minimum distance to illuminated surfaces: 0.3 m (11 in.)
Thermal	Temperature range, Operating	-40° to +50°C (-40° to +122°F)
	Temperature range, Start-up	-20° to +50°C (-4° to +122°F)
Thermal	Temperature range, Storage	-40° to +80°C (-40° to +176°F)
	Humidity	98%
Thermal	Humidity	98%
	Cooling	Passive
Connections	DMX data in/out	1 x 5 meter cable for DMX in and out
	Power	1 x 5 meter cable with bare ends
Conforms to	UL Std. 1573 ***	EN 60598-1, EN 60598-2-17, EN 62471, EN 60529
	2014/35/EU: Low Voltage Directive 2014/30/EU: EMC Directive RoHS2 Directive	EN 55103-1, EN 55103-2, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3 2011/65/EU
Included items	Included items	One Omega bracket with 1/4-turn fasteners
		User manual
Fixtures and accessories	Fixtures	Order no: 80100201 - G-1 Beam, POI, BL
		Order no: 80100211 - G-1 Beam, POI, WH,
Fixtures and accessories	Wireless transmitter	Order no: 80100291 - G-1 Beam, POI, CU,
		Order no: 80070229 - Lumen Radio CRMX transmitter (DMX only)
Fixtures and accessories	Cables	Order no: 83062011 - SGM USB uploader cable
		Order no: 83060602 - Omega bracket
Fixtures and accessories	Bracket	Order no: 83061707 - Ceiling mount for G-1
		Order no: 82051004 - Flightcase for 4 pcs. G-1 Beam
Fixtures and accessories	Flightcase	

*Figures provided by manufacturer and obtained under manufacturer's test conditions

**Photometrics / SGM Illumination Lab 1.6.0.0

***Pending

BL = Black (RAL 9004)

WH = White (RAL 9010)

CU = Custom Color (Any RAL color)