

P-5 W POI

LED Wash Light

Specifications		
Optics	Light source	44 x High power 10W Cool White LEDs (6,400K)
	LEDs expected lifetime	50,000 hours*
	Interchangeable lens option	15°, 21° & 43°
Photometric	Light output	24,900 lumen (43° lens)
	Efficacy	55 lm/W
Features	Tilt	0 - 190°
	Dehumidifier	Base / Head
	Power/DMX indicator	Base
Electrical	AC Power	208 - 240 V Nominal 50/60 Hz
	Maximum power consumption	450 W (all LEDs on)
	Typical power consumption	420 W (all LEDs on)
	Power factor	0.98 PF (230 V)
Programming and Control	Protocol	USITT DMX512 A
	Setting and addressing	RDM Software upgradeable via Uploader cable (P/N:83062011)
	DMX channels	1 or 2 DMX channels
Physical	Dimensions (L x H x W)	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in)
	Weight	8.9 kg (19.6 lbs.)
	Material	Aluminium
	Lens	PE and tempered glass front
	IP class	IP66
	Corrosion class	C5-M
	Color options	White – RAL 9010 Black – RAL 9004 Custom color – any RAL
Installation	Mounting	Any
	Rigging possibilities	Floor stand (included) or hanging (Omega Clamps included)
	Safety features	Bottom mount for Safety wire
Thermal	Temperature range, Operating	-40° to +50°C (-40° to +122°F)
	Temperature range, Start-up	-20° to +50°C (-4° to +122°F)
	Temperature range, Storage	-40° to +80°C (-40° to +176°F)
	Humidity (max.)	98%
Cooling		Active, forced air, temperature-regulated, low noise
Connections	DMX data in/out	1 x 5 meter cable for DMX in and out
	Power	1 x 5 meter cable with bare ends
Conforms to	2014/35/EU: Low Voltage Directive	EN 60598-1, EN 60598-2-17, EN 62471, EN 60529
	2014/30/EU: EMC Directive	EN 55103-1, EN 55103-2, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3
	RoHS2 Directive	2011/65/EU
Included Items	Included Items	Floor Stand (incl. screws) 2 pcs Omega brackets User manual
Fixtures and Accessories	Fixtures	Order no: 80030710 - P-5 W Wash, 43deg, POI, BL
		Order no: 80030740 - P-5 W Wash, 43deg, POI, WH
		Order no: 80030780 - P-5 W Wash, 43deg, POI, CU
		Order no: 80030711 - P-5 W Wash, 21deg, POI, BL
		Order no: 80030741 - P-5 W Wash, 21deg, POI, WH
		Order no: 80030781 - P-5 W Wash, 21deg, POI, CU
		Order no: 80030712 - P-5 W Wash, 15deg, POI, BL
		Order no: 80030742 - P-5 W Wash, 15deg, POI, WH
		Order no: 80030782 - P-5 W Wash, 15deg, POI, CU
Lens/s	Order no: 83061118 - P-5, Lens kit (43°)	
	Order no: 83061117 - P-5, Lens kit (21°)	
Brackets	Order no: 83061116 - P-5, Lens kit (15°)	
	Order no: 83060603 - BCC-2 Dual bracket	
	Order no: 83060604 - BCC-4 Quad bracket	
Floorstand	Order no: 83060602 - Omega bracket	
	Order no: 83060610 - Floorstand for P, Q and X series with 1/4-turn fasteners	
Barndoor	Order no: 83061119 - Accessory Holder P Series	
	Order no: 83061120 - Barndoor 4-way	
	Order no: 83061121 - Barndoor 8-way	
Cables	Order no: 83061122 - Color frame	
	Order no: 83062011 - SGM USB uploader cable	
	Order no: 82051501 - Flight case for 4 pcs of P-5/Q-7/X-5	
Flight case	Order no: 82051502 - Flight case for 4 pcs of P-5/Q-7/X-5 incl. Barndoors	

*Photometrics / SGM Illumination Lab

Figures provided by manufacturer and obtained under manufacturer's test conditions

BL = Black (RAL 9004)

WH = White (RAL 9010)