

## R-2 W, 3000K Rail Light

Specifications	Optics	Light source LEDs expected lifetime Interchangeable lens option	3,000K 50,000 hours* 25° / 35°
	Photometric	Light output Optical efficacy CRI	2,600 lm 93 lm/W >80
Features	Pan / Tilt		330° / 270°
	Electrical	AC power nominal AC power max rating Maximum power consumption Typical power consumption Power factor	100 - 240 V 50/60 Hz 90 - 264V 50/60Hz 32W 28W 0.90 PF (230 V)
Programming and control	Protocol Setting and addressing DMX channel		CRMX, W-DMX™ G2, W-DMX™ G3, W-DMX™ G4, W-DMX™ G4S Wireless DMX (LumenRadio) Software upgradable via wireless 1
	Physical	Dimensions (L x W) Spot diameter Weight Material Lens IP class	224 x 187 mm (8.8 x 7.4 in) Ø 104 mm (4.1 in) 1 kg (2.2 lbs.) Aluminium, stainless steel, ABS PMMA IP20
Installation	Mounting Compatibility Orientation		3-circuit track system Staff, Norlux, Global, Nuco and Nordic Any
	Thermal	Temperature range, Operating Humidity (max.) Cooling	-10° to +40°C (-14° to +104°F) 95% Passive cooling
Connections	Power DMX		Track mount adapter Wireless (LumenRadio)
	Conforms to	2006/95/EC: Low Voltage Directive 1999/5/EC: R&TTE Directive RoHS2 Directive	EN 60598-1, EN 60598-2-1, EN 60598-2-17, EN 62471 EN301489-1, EN301489-3, EN300328 2011/65/EU
Included items	Included items		User manual
Fixtures and accessories	Fixtures		Order no: 84010101 - R-2 W, 3000K, white, 25 deg Order no: 84010102 - R-2 W, 3000K, black, 25 deg
	Accessories		Order no: 83062011 - SGM USB uploader cable Order no: 80070229 - LumenRadio CRMX transmitter (DMX only)

\*Figures provided by manufacturer and obtained under manufacturer's test conditions